



DESCRIPTION

The N6081 Series controllers are compact and user-friendly units providing remote control for the Stellar Outdoor Unit amplifier.

FEATURES

- User-friendly - Easy to use controls with clear, high visibility displays.
- Small, light and very compact unit.
- Internally powered from the amplifier.
- Dual power reading (dBW/watts).
- Ready to use out of the box (see note 1).

MECHANICAL SPECIFICATION

Weight	0.5 kg
Dimensions:	
height	44 mm
depth	50 mm
width	483 mm
Cooling	natural

CONTROLS

- Front panel control keys:
- Off mode select (OFF)
 - Standby mode select (STBY)
 - Transmit mode select (XMIT)
 - Function select switch
 - Gain control (see note 2)
 - Rotary shaft encoder for gain control (N6081 only)

DOCUMENTATION

An operation manual is supplied with each unit.

Whilst e2v technologies has taken care to ensure the accuracy of the information contained herein it accepts no responsibility for the consequences of any use thereof and also reserves the right to change the specification of goods without notice. e2v technologies accepts no liability beyond that set out in its standard conditions of sale in respect of infringement of third party patents arising from the use of tubes or other devices in accordance with information contained herein.

e2v technologies limited, Waterhouse Lane, Chelmsford, Essex CM1 2QU England Telephone: +44 (0)1245 493493 Facsimile: +44 (0)1245 492492
e-mail: enquiries@e2vtechnologies.com Internet: www.e2vtechnologies.com Holding Company: e2v holdings limited

e2v technologies inc. 4 Westchester Plaza, PO Box 1482, Elmsford, NY10523-1482 USA Telephone: (914) 592-6050 Facsimile: (914) 592-5148
e-mail: enquiries@e2vtechnologies.us

ENVIRONMENTAL

For operation outside these parameters, contact e2v technologies for guidance.

Operating temperature	0 to +50 °C
Storage temperature	-40 to +70 °C
Vibration	MIL-STD-810E
	Common carrier and field transportation
Shock	IEC publication 68-2-27 Part 2 Test Ea 25g
Electromagnetic compatibility	EMC directive
	89/336/EEC ETS 300 327
Safety	Low voltage directive 73/23/EEC BS EN 60950

CONNECTOR

Amplifier interface 15-pin D-type socket

FRONT PANEL DISPLAY

Backlit LCD display showing:

- Forward power (watts)
- Forward power (dBW)
- Helix current (mA)

OPTIONS

N6081D allows remote control of a digital electronically variable attenuator (DEVA) when used in conjunction with an appropriate amplifier.

NOTES

1. Interconnecting cables are not provided as standard.
2. Gain control function is only applicable if specified as an option when purchasing amplifiers.